



|                                     |          |
|-------------------------------------|----------|
| Designation :                       | 31330XJ2 |
| Principal dimensions(mm)            |          |
| d1 :                                | 150      |
| D :                                 | 320      |
| B :                                 | 82       |
| Basic load ratings(KN)              |          |
| dyc(Cr) :                           | 781      |
| stc(Cor) :                          | 1020     |
| Pu :                                | 100      |
| Speed ratings(rpm)                  |          |
| Speed Ratings :                     | 1400     |
| Limiting Speed :                    | 2000     |
| Weight(Kg) :                        | 29,5     |
| ISO335                              |          |
| Dimensions (ABMA) :                 | 7GB      |
| Dimensions (mm)                     |          |
| d :                                 | 150      |
| d1□ :                               | 234      |
| B :                                 | 75       |
| C :                                 | 50       |
| r1,2(min) :                         | 5        |
| r3,4(min) :                         | 4        |
| a :                                 | 96       |
| Abutment and fillet dimensions (mm) |          |
| da(max) :                           | 181      |
| db(min) :                           | 170      |
| Da(min) :                           | 251      |
| Da(max) :                           | 303      |
| Db(min) :                           | 300      |
| Ca(min) :                           | 9        |
| Cb(min) :                           | 32       |
| ra(max) :                           | 4        |
| rb(max) :                           | 3        |
| Value                               |          |
| e :                                 | 0,83     |
| Y :                                 | 0,72     |
| Yo :                                | 0,4      |