



|                                     |        |
|-------------------------------------|--------|
| Designation :                       | 32056X |
| Principal dimensions(mm)            |        |
| d1 :                                | 280    |
| D :                                 | 420    |
| B :                                 | 87     |
| Basic load ratings(KN)              |        |
| dyc(Cr) :                           | 1210   |
| stc(Cor) :                          | 2360   |
| Pu :                                | 200    |
| Speed ratings(rpm)                  |        |
| Speed Ratings :                     | 1000   |
| Limiting Speed :                    | 1300   |
| Weight(Kg) :                        | 40,5   |
| ISO335                              |        |
| Dimensions (ABMA) :                 | 4FC    |
| Dimensions (mm)                     |        |
| d :                                 | 280    |
| d1□ :                               | 348    |
| B :                                 | 87     |
| C :                                 | 65     |
| r1,2(min) :                         | 5      |
| r3,4(min) :                         | 4      |
| a :                                 | 89     |
| Abutment and fillet dimensions (mm) |        |
| da(max) :                           | 305    |
| db(min) :                           | 302    |
| Da(min) :                           | 370    |
| Da(max) :                           | 400    |
| Db(min) :                           | 402    |
| Ca(min) :                           | 14     |
| Cb(min) :                           | 22     |
| ra(max) :                           | 4      |
| rb(max) :                           | 3      |
| Value                               |        |
| e :                                 | 0,46   |
| Y :                                 | 1,3    |
| Yo :                                | 0,7    |