



|                                     |         |
|-------------------------------------|---------|
| Designation :                       | 33110/Q |
| Principal dimensions(mm)            |         |
| d1 :                                | 50      |
| D :                                 | 85      |
| B :                                 | 26      |
| Basic load ratings(KN)              |         |
| dyc(Cr) :                           | 100     |
| stc(Cor) :                          | 122     |
| Pu :                                | 13,4    |
| Speed ratings(rpm)                  |         |
| Speed Ratings :                     | 6000    |
| Limiting Speed :                    | 7500    |
| Weight(Kg) :                        | 0,59    |
| ISO335                              |         |
| Dimensions (ABMA) :                 | 3CE     |
| Dimensions (mm)                     |         |
| d :                                 | 50      |
| d1□ :                               | 67,9    |
| B :                                 | 26      |
| C :                                 | 20      |
| r1,2(min) :                         | 1,5     |
| r3,4(min) :                         | 1,5     |
| a :                                 | 20      |
| Abutment and fillet dimensions (mm) |         |
| da(max) :                           | 57      |
| db(min) :                           | 57      |
| Da(min) :                           | 74      |
| Da(max) :                           | 78      |
| Db(min) :                           | 82      |
| Ca(min) :                           | 4       |
| Cb(min) :                           | 6       |
| ra(max) :                           | 1,5     |
| rb(max) :                           | 1,5     |
| Value                               |         |
| e :                                 | 0,4     |
| Y :                                 | 1,5     |
| Yo :                                | 0,8     |